



## Second Petroleum Spray Paint TDS

**Product Description:** 7CF® The product is made from thermoplastic acrylic resin and it can be applied by aerosol spray and provide films with excellent performance such as excellent weather resistance, good leveling, strong coverage, fast drying, high build and match well with many types of primers.

**Applications:** Widely used for all interior/exterior applications, for surface finishing of iron & steel, plastics, metals, surface-treated wood, glass and other substrates.

**Features & Benefits:**

- Low flash point & burning point
- Fast drying
- Simple construction operation
- Good spray atomization
- High spray rate
- High film fullness
- Excellent decorative effect
- Superior adhesion and durability
- Excellent protection against impact, UV etc.

**Unit Package Description:** 10oz (283g)

**Brand:** 7CF

**Appearance:** Film flat and smooth, no mechanical impurities, accord with the confirmed sample.

**Drying condition:** Touch dry  $\leq$  15 minutes, finger press dry  $\leq$  1 hours

**Recommended Thickness:** 18-25 $\mu$

**Volume Solid:** 15-25%

**Specific Gravity:** 0.90-1.15

**Adhesion:**  $\leq$  2

**Hardness:**  $\geq$  HB

**Gloss:** Gloss  $\geq$  80; Matt accord with the confirmed sample

**Flexibility:**  $\leq$  1mm

**Spraying rate:**  $\geq$  98%

**Flash point:** Low

**Burning point:** Low

**Shelf Life:** Three Years